















## STOREFRONT SYSTEMS

						
SERIES	SMI-45	SMI-245	SMI-090	SMI-175	SMI-090	FS-300
Application	Non-Impact	Non-Impact	Non-Impact	Impact Blast Resistant*	Impact Blast Resistant* Bullet Resistant Flood Resistant*	Impact Blast Resistant* Bullet Resistant Flood Resistant*
Profile	1 3/4" x 4 1/2"	2" x 4 1/2"	1 3/4" x 4 1/2"	1 3/4" x 4 1/2"	1 3/4" x 4 1/2"	1 1/2" x 4 1/2"
Glazing Options	1/4", 3/8"	1/4", 1/2", 1" IG	1/4", 1" IG	9/16"	9/16", 1 5/16"	9/16", 1 5/16"
Design Loads/ Water	+80/-80 12 lbs.	+50/-50 7.5 lbs.	+120/-120 18 lbs.	+100/-120 15 lbs.	+100/-120 15 lbs.	+120/-135 18 lbs.
Max Panel	36" x 144"	48" x 120"	36" x 144"	60" x 120"	48" x 120"	60" x 144"
Product Approval	FBC NOA	FBC	FBC NOA	FBC NOA	FBC NOA	FBC NOA
Features	<ul style="list-style-type: none"> <li>Flush glazed storefront</li> <li>No exposed fasteners</li> <li>Can be unitized</li> </ul>	<ul style="list-style-type: none"> <li>Flush glazed storefront</li> <li>1" IG or 1/4" glazing</li> <li>Screw spline assembly</li> </ul>	<ul style="list-style-type: none"> <li>1" IG glazing</li> <li>No exposed fasteners</li> <li><b>Can Be Pre-Glazed</b></li> </ul>	<ul style="list-style-type: none"> <li>Sturdy impact storefront system</li> <li>Only 4 extrusions</li> <li>Screw spline assembly</li> <li><b>Can Be Pre-Glazed</b></li> </ul>	<ul style="list-style-type: none"> <li>Variable glazed system</li> <li>9/16" or 1 5/16" glazing</li> <li>Screw spline assembly</li> <li>Optional thermal break</li> <li><b>Can Be Pre-Glazed</b></li> <li>P-TAC approval</li> </ul>	<ul style="list-style-type: none"> <li>Front set storefront system</li> <li>9/16" or 1 5/16" glazing</li> <li>Can be thermally broken</li> <li><b>Can Be Pre-Glazed</b></li> <li>Screw spline or shear block assembly</li> </ul>

\*Storefront can be shipped as stock lengths, pre-fabbed or pre-glazed  
 \*Flood and blast resistant use of product requires site specific engineering by a third party  
**Pre-glazed units can be offered as part of Aldora's Rapid Glaze, Buy-in to Dry-in, storefront delivery system**



## ENTRANCE DOORS

						
SERIES	McKinley	DENALI	K2-Breeze	K2LM	K2 Summit Outswing	K2 Summit Inswing
Application	Non-Impact	Non-Impact	Impact	Impact	Impact	Impact
Stiles	2 1/8"	3 1/2"	3 1/2"	3 1/2"	3 1/2"	3 1/2"
Top Rail	2 3/4"	2 3/4"	4 7/8"	4 7/8"	4 7/8"	4 7/8"
Bottom Rail	3 1/2"	4 1/2"	6 3/8"	6 3/8"	6 3/8" or 10"	6 3/8" or 10"
Glazing Options	1/4, 3/8, 1" IG	1/4", 3/8", 1", IG	9/16"	9/16"	9/16", 1 5/16"	9/16", 1 5/16"
Design Loads/ Water	+80/-80 N/A	+80/-80 N/A	+90/-120 15 lbs.	+100/-100 15 lbs.	+100/-100 15 lbs.	+80/-100 N/A
Max Panel	6'0" x 8'0"	6'0" x 8'0"	3'6" x 8'11"	8'0" x 10'0"	8'0" x 10'0"	6'0" x 7'8"
Product Approval	FBC NOA	FBC NOA	FBC NOA	FBC NOA	FBC NOA	FBC NOA
Optional Features	<ul style="list-style-type: none"> <li>Panic options</li> <li>7" bottom rail</li> <li>Overhead concealed</li> <li>Hinges or Pivots</li> </ul>	<ul style="list-style-type: none"> <li>Panic options</li> <li>Residential latch lever</li> <li>Overhead concealed closer, 7" bottom rail</li> </ul>	<ul style="list-style-type: none"> <li>Bottom panel options</li> <li>Residential latch lever</li> </ul>	<ul style="list-style-type: none"> <li>Residential latch lever</li> <li>Water rating preparation</li> <li>Step up threshold</li> <li>Astragals (pairs)</li> <li>Overhead concealed closer</li> </ul>	<ul style="list-style-type: none"> <li>9/16" or 1 5/16" glass</li> <li>Optional 3/4" jamb</li> <li>4 Panic options</li> <li>Continuous gear hinge</li> <li>Overhead concealed closer</li> <li>Residential latch lever</li> <li>Optional 10" bottom rails</li> </ul>	<ul style="list-style-type: none"> <li>9/16" or 1 5/16" glass</li> <li>Optional 3/4" jamb</li> <li>Continuous gear hinge</li> <li>Overhead concealed closer</li> <li>Residential latch lever</li> <li>Optional 10" bottom rails</li> </ul>

Standard colors include clear anodized, bronze anodized and white paint