



SPARTA SGD4130 SLIDING GLASS DOOR

- Finishes: Powder paint white and bronze
- Florida Product Approval
- Extruded screens
- Aluminum extruded square bead
- Design pressures: +55/-65
- Max panel size: 4' x 8'
- Nominal frame depth:
 - 2-track: 5"
 - 3-track: 7"
- Muntin types/configurations:
 - CGI surface applied (low profile exterior and flat bar interior)
 - Standard patterns
- Glass:
 - 7/16" A/H .090 PVB
 - 7/16" H/H .090 PVB

COMMON SIZES

CONFIGURATION	SIZE CODE	WIDTH	HEIGHT	CONFIGURATION	SIZE CODE	WIDTH	HEIGHT
2P2T	4068	48	80	4P2T	10068	118 5/8	80
2P2T	5068	60	80	4P2T	10070	118 5/8	84
2P2T	6068	72	80	4P2T	10080	118 5/8	96
2P2T	8068	96	80	4P2T	12068	142 5/8	80
2P2T	4070	48	84	4P2T	12070	142 5/8	84
2P2T	5070	60	84	4P2T	12080	142 5/8	96
2P2T	6070	72	84	4P2T	16068	190 5/8	80
2P2T	8070	96	84	4P2T	16070	190 5/8	84
2P2T	4080	48	96	4P2T	16080	190 5/8	96
2P2T	5080	60	96				
2P2T	6080	72	96				
2P2T	8080	96	96				
3P2T	7668	91	80				
3P2T	7670	91	84				
3P2T	7680	91	96				
3P2T	9068	109	80				
3P2T	9070	109	84				
3P2T	9080	109	96				
3P2T	12068	145	80				
3P2T	12070	145	84				
3P2T	12080	145	96				
3P3T	7668	87 1/16	80				
3P3T	7670	87 1/16	84				
3P3T	7680	87 1/16	96				
3P3T	9068	105 1/16	80				
3P3T	9070	105 1/16	84				
3P3T	9080	105 1/16	96				
3P3T	12068	141 1/16	80				
3P3T	12070	141 1/16	84				
3P3T	12080	141 1/16	96				

NFRC CERTIFIED ENERGY VALUES				GRIDS			
Laminated		U Factor	SHGC	VT	U Factor	SHGC	VT
7/16	Clear	1.03	.54	.62	1.03	.41	.46
7/16	Gray	1.03	.42	.35	1.03	.32	.26
7/16	Bronze	1.03	.45	.41	1.03	.34	.30
7/16	Mist	1.03	.54	.62	1.03	.41	.46
7/16	Clear Energy Coating	1.03	.27	.43	1.03	.21	.33
7/16	Gray Energy Coating	1.03	.22	.25	1.03	.18	.19
7/16	Bronze Energy Coating	1.03	.23	.28	1.03	.18	.21
7/16	Mist Energy Coating	1.03	.27	.43	1.03	.21	.33

SILL DETAILS

